

RESOLTECH 1410-1417 and Accelerator AC140

Hot curing epoxy system

RST 1410 is a low viscosity cycloaliphatic epoxy resin

RST 1417 is an anhydride hardener

Accelerator AC140 is an imidazole accelerator

Applications

High performance composite parts

Properties

Extremely low-viscosity, anhydride-cured, reactive diluent free matrix system with a long pot life. The reactivity of the system is adjustable by variation of the accelerator content. The system is easy to process, has good fibre impregnation properties and exhibits excellent mechanical, dynamic and thermal properties. It has an excellent chemical resistance especially to acids at temperatures up to 80 °C. Displays very good temperature resistance after post cure.

Processing

Filament Winding, Pultrusion, Pressure Moulding

Key Data

RST 1410

Aspect (visual)	clear yellow liquid
Viscosity at 25 °C (ISO 12058-1)	350 - 450 [mPa s]
Epoxy index (ISO 3001)	7.00 - 7.63 [eq/kg]
Epoxy equivalent (ISO 3001)	131 - 143 [g/eq]
Density at 25 °C (ISO 1675)	1.17 [g/cm ³]
Flash point (ISO 2719)	> 150 [°C]
Storage temperature	2 - 40 °C
(see expiry date on original container)	

RST 1417

Aspect (visual) :	clear liquid
Colour (Gardner, ISO 4630) :	≤2
Viscosity at 25 °C (ISO 12058-1) :	50 - 100 [mPa s]
Density at 25 °C (ISO 1675) :	1.20 - 1.25 [g/cm ³]
Flash point (ISO 2719) :	195 [°C]
Storage temperature :	2 - 40 °C [°C]

Accelerator AC140

Aspect (visual) :	clear liquid
Colour (Gardner, ISO 4630) :	≤9
Viscosity at 25 °C (ISO 12058-1) :	≤50 [mPa s]
Density at 25 °C (ISO 1675) :	0.95 - 1.05 [g/cm ³]
Flash point (ISO 2719) :	92 [°C]
Storage temperature	2 - 40 °C [°C]

Storage

Provided that RST 1410, RST 1417 and Accelerator AC140 are stored in a dry place in their original, properly closed containers at the above mentioned storage temperatures they will have the shelf lives indicated on the labels. Partly emptied containers should be closed immediately after use. Because RST 1417 is sensitive to moisture, storage containers should be ventilated with dry air only. RST 1410 which has crystallized and looks cloudy can be restored to its original state by heating to 60 - 80 °C.

Processing data

Mix ratio

Components

Parts by weight

Parts by volume

RST 1410

100

100

RST 1417

115

110

AC140

0.5 – 2

0.6 - 2.4

We recommend that the components are weighed with an accurate balance to prevent mixing inaccuracies which can affect the properties of the matrix system. The components should be mixed thoroughly to ensure homogeneity. It is important that the side and the bottom of the vessel are incorporated into the mixing process.

Initial mix viscosity

(Hoeppler, ISO 9371B)

[°C]
at 25

[mPa s]
150 - 250

RST 1410

[pbw]

100

100

RST 1417

[pbw]

115

115

AC140

[pbw]

1

2

Pot life

(Tecam, 100 ml,
65 % RH)

[°C]
at 23
at 40

[days]
≥ 2

[days]
≥ 2
1.0 - 1.5

Gel time

(Hot plate)

[°C]
at 90
at 100
at 120
at 140

[min]
100 - 140
55 - 65
15 - 17
6 - 8

[min]
60 - 80
25 - 30
8 - 10
3 - 4

The values shown are for small amounts of pure resin/hardener mix. In composite structures the gel time can differ significantly from the given values depending on the fibre content and the laminate thickness.

Typical cure cycles

1 - 2 h 100 °C + 6 h 160 °C
or 1 - 2 h 100 °C + 4 - 6 h 180 °C

The optimum cure cycle has to be determined case by case depending on the processing and the economic requirements.

Properties of the cured, neat formulation

The values below were obtained with a formulation using 2 pbw AC140

Glass transition

Temperature

(TMA, 10 K/min)

Cure:


TG [°C]

1 h 100 °C + 4 h 160 °C	189
1 h 100 °C + 6 h 160 °C	190
1 h 100 °C + 8 h 160 °C	191
1 h 100 °C + 2 h 180 °C	200
1 h 100 °C + 4 h 180 °C	201
1 h 100 °C + 6 h 180 °C	206
1 h 120 °C + 4 h 160 °C	191
1 h 120 °C + 6 h 160 °C	193
1 h 120 °C + 8 h 160 °C	195
1 h 120 °C + 2 h 180 °C	202
1 h 120 °C + 4 h 180 °C	204
1 h 120 °C + 6 h 180 °C	208

(Kinetech, 3 K/min)

1 h 100 °C + 2 h 180 °C

230 °C



Tensile test

(ISO 527)

Cure:

2 h 120 °C
+ 6 h 160 °C

1 h 100 °C
+ 6 h 180 °C

1 h 120 °C
+ 2 h 180 °C

Tensile strength
Elongation at tensile
strengthTensile modulus

MPa
%
MPa

45 – 65
1.0 - 1.5
2950 – 3050

48 – 60
1.8 - 2.5
2900 – 3000

42 – 53
1.6 - 2.1
2900 – 3000


Flexural test
 (ISO 178)

Cure:

 2 h 120 °C
 + 6 h 160 °C

 1 h 100 °C
 + 6 h 180 °C

Flexural strength	MPa	80 – 105	110 – 135
Elongation at flexural strength	%	2.3 - 3.6	3.8 - 5.0
Ultimate strength	MPa	80 – 105	110 – 135
Ultimate elongation	%	2.3 - 3.6	3.9 - 5.2
Flexural modulus	MPa	2900 – 3100	2980 - 3120

Cure:

 2 h 120 °C
 + 6 h 160 °C

Fracture properties
Bend notch test
 (PM 258-0/90)

 Fracture toughness K1C
 Fracture energy G1C

 MPa
 mJ/m2

 0.5 - 0.54
 72 – 84

Water absorption
 (ISO 62)

Immersion:

Cure:

 1 h 120 °C
 + 6 h 160 °C

4 days H2O 23 °C	%	0.50 - 0.65
10 days H2O 23 °C	%	0.80 - 1.10
30 min H2O 100 °C	%	0.20 - 0.30
60 min H2O 100 °C	%	0.35 - 0.45

Coefficient of
linear thermal
expansion
 (DIN 53 752)

Mean value:

Cure:

 1 h 100 °C
 + 6 h 180 °C

 1 h 120 °C
 + 2 h 180 °C

from 20 - 100 °C	[10 ⁻⁶ /K]	62 – 65	63 – 65
from 100 - 130 °C	[10 ⁻⁶ /K]	66 – 68	66 – 69
from 100 - 170 °C	[10 ⁻⁶ /K]	70 – 72	71 - 73


résoltech
 ADVANCED TECHNOLOGY RESINS